

MATERIAL SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product Name: Bob's Adhesive Remover
Distributor: Performance Screen Supply
Distributor's address: 919 Route 33, Freehold, New Jersey 07728
Telephone number for information: 1-800-659-8337
Telephone number for emergencies: Chemtel - 1-800-255-3924
Chemical: The precise composition of this product is proprietary information. A more complete disclosure will be provided to a physician in the event of a medical emergency. Contains fatty acids C16-18 and C18 unsaturated, Methyl Esters CAS-67762-38-3 Denatured corn ethanol
Preparer: Performance Screen Supply - EHS Department **Prepare Date:** 10/16/01

SECTION 2: HAZARDOUS INGREDIENTS

<u>Material</u>	<u>CAS</u>	<u>%</u>
None		

SARA Hazard: Title III Section 313: not listed

SECTION 3: HEALTH INFORMATION

Effects of Overexposure:

Inhalation: May cause irritation to respiratory system.
Ingestion: May cause irritation of the digestive tract.
Eye Contact: May cause eye irritation
Skin Contact: May cause skin irritation.
Carcinogenicity: Not listed by NTP,IARC,OSHA

SECTION 4: OCCUPATIONAL EXPOSURE LIMITS

PEL: No OSHA PEL **TLV:** No ACGIH TLV

SECTION 5: EMERGENCY FIRST AID PROCEDURE

Follow standard first aid procedures:

Swallowing: Do not induce vomiting. Call physician or poison control center.
Skin Contact: Wash affected area with soap and water. Remove contaminated clothing and wash before reuse. If irritation persists, get medical attention.
Eye Contact: Flush eyes with cool water for at least 15 minutes. Do not let victim rub eyes. Obtain medical aid.
Inhalation: Immediately remove victim to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately.

SECTION 6: PHYSICAL DATA

Boiling Point: 350°F
Melting Point: n/a
Vapor Pressure: n/a
Specific Gravity: 0.885
Appearance and Color: Pale orange liquid
Odor: Citrus odor
Solubility in Water: Emulsifiable
Evaporation Rate: Less than 1 (n-butyl acetate=1)

SECTION 7: FIRE AND EXPLOSION HAZARDS

Flash Point & Method Used: 150°F
Flammable Limits: Not applicable
NFPA Rating: No NFPA rating
HMIS Rating: Health: 1 Fire: 2 Reactivity: 0
Special Fire Fighting Procedures & Precautions: Protective clothing and self-contained breathing apparatus should be worn when fires involve chemicals.
Unusual Fire & Explosion Hazards: Keep containers cool with water fog.

SECTION 8: REACTIVITY

Stability: Stable
Hazardous Polymerization: Will not occur
Materials to avoid: Strong oxidizers.
Conditions to avoid: Extreme heat.

SECTION 9: EMPLOYEE PROTECTION

Control Measures:	Adequate ventilation
Respiratory Protection:	None required for normal usage
Protective Clothing:	As required
Eye Protection:	Chemical splash goggles
Ventilation:	Local exhaust; preferred, Mechanical; acceptable
Protective gloves:	Nitrile or Neoprene
Work/Hygienic Practices:	Practice reasonable care and cleanliness. Avoid prolonged breathing of vapors.

SECTION 10: ENVIRONMENTAL PROTECTION

Environmental Precautions:	Avoid uncontrolled release of this material to the environment.
Spill or Leak Precautions:	Contain spilled material. Transfer to secure containers. Where necessary, use suitable non-reactive absorbent media.
Waste Disposal:	Dispose of according to federal, state and/or local requirements.

SECTION 11: REGULATORY CONTROLS

DOT Classification:	Class 55
DOT Proper Shipping Name:	Compounds, cleaning NMFC 04858003

SECTION 12: PRECAUTIONS, HANDLING, STORAGE & USAGE

None known.

The information above is believed to be accurate and represents the best information currently available to us. However, Performance Screen Supply, LLC makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.