

MATERIAL SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product Name: Bob's Soy Bean Wash
Distributor: Performance Screen Supply
Distributor's address: 919 Route 33, Freehold, New Jersey 07728
Telephone number for information: 1-800-659-8337
Telephone number for emergencies: Chemtel - 1-800-255-3924
Chemicals: Fatty acids C16-18 and C18 unsaturated
Methyl esters CAS#67762-38-3 and mild surfactants
Preparer: Performance Screen Supply - EHS Department **Prepare Date:** 06/22/01

SECTION 2: HAZARDOUS INGREDIENTS

<u>Material</u>	<u>CAS</u>	<u>%</u>
None		

SARA Hazard: Title III Section 313: not listed

FIRE - (Section 311/312) None noted

SECTION 3: HEALTH INFORMATION

Effects of Overexposure:

Inhalation: No known problems
Ingestion: May cause irritation of the digestive tract.
Eye Contact: May cause eye irritation
Skin Contact: Not classified as a primary skin irritant or corrosive material
Carcinogenicity: Not listed by NTP, IARC, OSHA

SECTION 4: OCCUPATIONAL EXPOSURE LIMITS

PEL: No OSHA PEL

TLV: No ACGIH TLV

SECTION 5: EMERGENCY FIRST AID PROCEDURE

Follow standard first aid procedures:

Swallowing: Call physician or poison control center.
Skin Contact: Wash affected area.
Eye Contact: Flush eyes with cool water for at least 15 minutes. Do not let victim rub eyes.
Inhalation: Immediately remove victim to fresh air. Get medical attention immediately.

SECTION 6: PHYSICAL DATA

Boiling Point: Over 400°F (204°C) at 760 mm Hg pressure
Melting Point: -1°C
Vapor Pressure: Less than 5mm HG at 72°F
Specific Gravity: 0.91 at 25°C
Appearance and Color: Water white to yellowish liquid
Odor: Light musty odor
Solubility in Water: Emulsifiable
Evaporation Rate: Less than 1 (n-butyl acetate=1)

SECTION 7: FIRE AND EXPLOSION HAZARDS

Flash Point & Method Used: 425°F (218°C) (PMCC)
Flammable Limits: Not applicable
NFPA Rating: No NFPA rating
HMIS Rating: Health: 0 Fire: 1 Reactivity: 0

Special Fire Fighting Procedures & Precautions:

Unusual Fire & Explosion Hazards: Treat as oil fire. Use water spray, dry chemical, foam, or carbon dioxide. Rags soaked with any solvent present a fire hazard and should always be stored in UL listed or Factory Mutual approved, covered containers. Improperly stored rags can create conditions that lead to oxidation. Oxidation, under certain conditions can lead to spontaneous combustion. This product contains anti-oxidants to retard oxidation.

SECTION 8: REACTIVITY

Stability: Stable
Hazardous Polymerization: None likely
Materials to avoid: Strong oxidizing agents, rags soaked with other solvents or chemicals.
Hazardous Decomposition Products: CO₂, CO
Conditions to avoid: None known

SECTION 9: EMPLOYEE PROTECTION

Control Measures: Adequate ventilation

Respiratory Protection: None required for normal usage
Protective Clothing: As required
Eye Protection: Safety glasses, goggles or face shield

SECTION 10: ENVIRONMENTAL PROTECTION

Environmental Precautions: Avoid uncontrolled release of this material to the environment.
Spill or Leak Precautions: Contain spilled material. Transfer to secure containers. Where necessary, use absorbent media.
Waste Disposal: Dispose of according to federal, state and/or local requirements.

SECTION 11: REGULATORY CONTROLS

DOT Classification: Class 65
DOT Proper Shipping Name: Fatty acid esters
Other Regulatory Requirements: Listed in TSCA inventory

SECTION 12: PRECAUTIONS, HANDLING, STORAGE & USAGE

No special precautions necessary.

The information above is believed to be accurate and represents the best information currently available to us. However, Performance Screen Supply, LLC makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.