

del	HC301
Print Head	F1080*1
Number of Print-heads	1
Printing Width	≤30cm
Print color Configuration	CMYK+White
Applicable Media	PET film
Print Accuracy	720*108 dpi
Recommended speed	6Pass 1~1.5 m²/h
Ink Type	DTF ink
RIP Software	RIIN/Devstudio/Flexi
Color Management	ICC or density curve
operating System	Win7 and above system 64 bit
Print Interface	Gigabit network port
Trolley Anti-collision function	Both ends of the trolley are equipped with touch anti-collision alarm emergency stop devices
Automatic Feeding Function	Automatic tension discharging with probe induction
Paper Shortage Alarm Function	Paper shortage alarm during printing, automatic stop printing
Waste Ink Alarm Function	Automatic alarm when waste ink bottle is full
Circulating Stirring Function	The white ink is independently powered, and it can be stirred regularly and indefinitely in the off state
Ink Shortage Alarm Function	Automatic alarm for low ink volume of ink bottle
Print Platform Lighting Function	Print platform LED illumination
Platform Suction	Adjustable suction power
Temperature	20 - 30℃
Humidity	35-65%

Rated Power	0.5KW
Power Input	50HZ/60HZ,220V 15A
Net Weight	45KG
Gross Weight	55kg
Machine Dimensions	Length * width * height 820*641*362mm
Package Size	Length * width * height 1000*530*429mm