

Model	HC602
Print Head	EPSIN i3200-A1
Number of Print-heads	2
Printing Width	≤60cm
Print color Configuration	CMYK+White
Applicable Media	PET film
Print Accuracy	720*1200/720*1800/720*2400 dpi
Recommended speed	6Pass 9.5 m²/h 8Pass 7.5 m²/h
Ink Type	DTF ink
RIP Software	Devstudio/Flexi
Color Management	ICC or density curve
operating System	Win7、Win10、Win11
Print Interface	Gigabit network port
Trolley Anti-collision function	Both ends of the trolley are equipped with touch anti-collision alarm emergency stop devices
Automatic Feeding Function	Automatic tension discharging with probe induction
Paper Shortage Alarm Function	Paper shortage alarm during printing, automatic stop printing
Waste Ink Alarm Function	Automatic alarm when waste ink bottle is full
Circulating Stirring Function	The white ink is independently powered, and it can be stirred regularly and indefinitely in the off state
Ink Shortage Alarm Function	Automatic alarm for low ink volume of ink bottle
Print Platform Lighting Function	Print platform LED illumination
Automatic Lever Lifting and Paper Pressing Function	One key automatic lifting pressure bar for platform feeding
PC Assembly Function	Built in computer and monitor combined bracket, saving space
Platform Suction	Adjustable suction power
Temperature	15 - 30℃
Humidity	35-65%
Feeding Function	Automatic induction discharging
Rated Power	1KW
Power Input	50HZ/60HZ,220V 5A
Net Weight	160KG
Gross Weight	204KG
Machine Dimensions	Length * width * height 1336*658*1400mm
Package Size	Length * width * height 1470*1100*720mm